

Features

- ▶ 1/2.8" 2.13 Mega-Pixel SONY CMOS sensor
- ▶ Full HD Resolution
- ▶ D-WDR (Wide Dynamic Range)
- ▶ DNR (Digital Noise Reduction, 2D+3D)
- ▶ Lens Shading Compensation
- ▶ Privacy mask Function
- ▶ 3.6mm Fixed Lens
- ▶ Main Output 4 in 1
- ▶ DC 12 V



SPECIFICATION

SPECIFICATION	FK-H9011M
VIDEO	
Image Sensor	1/2.8" 2.13Mega-Pixel Sony CMOS sensor
Effective Pixels	1985(H) x 1105(V) = 2.19M (pixel)
Total Pixels	2001(H) x 1121(V) = 2.24M (pixel)
Max. Resolution	1920x1080
Lens Type	3.6 mm 3Mega Fixed Lens
Minimum Illumination	Color : 0.1 lux, BW : 0.5 lux, Color DSS : 0.002 lux, BW DSS : 0.0008 lux
S/N Ratio	More than 50dB
Electronic Shutter Speed	AUTO/MANUAL(1/50(60) – 1/50,000 sec)
Day/Night	True Day & Night (ICR)
IR LEDs	36IR LEDS
Video Out	AHD/CVI/TVI@1080P, 960H SD
FUNCTION	
Sens-UP	Yes / x2 ~ x32
WDR (Wide Dynamic Range)	D-WDR
BLC (Backlight Compensation)	Yes
HSBLC	Yes
Motion Detection	Yes (4 Zone)
Freeze	N/A
Privacy Masking	Yes (4 Programmable Zone, Box only)
Day&Night	Auto(AGC) / Color / B&W / EXTERN
White Balance	ATW, AWB, INDOOR, OUTDOOR, MANUAL
Digital Noise Reduction	2D+3DNR
Mirror	Yes
D-ZOOM	N/A
Sharpness	0~10 Level Adjustable
De-fog	Yes
Lens Shading (LSC)	Yes
OSD Language	Multi-language
ENVIRONMENTAL	
Out-Door Ready	IP 66
Operating Temperature	-10 °C~+50 °C / 10%~90%RH
ELECTRICAL	
Power Source	DC 12V
Power Consumption	T.B.D
MECHANICAL	
Dimensions(HxWxD)	68(∅)x 181mm(D) x 71.7(H)
Weight	T.B.D